

Facestock: Phthalate-Free Flexible Vinyl with Topcoat

DCM Dry Erase is our classic Magik-Stik product with a specially applied topcoat that transforms it into an easy-to-clean dry erase board. Virtually any surface can be transformed into one that accepts dry erase markers.

DCM Dry Erase is available in 3.5 mil white vinyl and 5.0 mil white vinyl.

Adhesive: Proprietary Removable/Repositionable System

DCM Dry Erase vinyl uses the same proprietary, water-based, microsphere adhesive formulation as our other Magik-Stik products. Magik-Stik adhesive works great on a variety of surfaces such as painted drywall, glass, metal, sanded wood (w/o lacquer), and most any non-textured or non-porous wall.

The minimum application temperature for DCM Dry Erase is 40°F, with a service temperature range of 40°F to 120°F.

Liner:

DCM Dry Erase is available on a 92# double-sided, poly-coated liner.

		Stocked Line	rs			
		50#	78#	83#	92#	8
						Pt.
Facestock:	3.5 White				Χ	
	5.0 White				Χ	

Item	Description
50# Liner	Semi-bleached, super-calendared, white kraft. (3.1 mil)
78# Liner	Clay-coated, super-calendared on one side, silicone-coated on the
	clay-coated side. (4.6 mil)
83# Liner	Silicone liner, clay-coated on both sides. (5.8 mil)
92# Liner	Heavyweight, bleached kraft, poly-coated on both sides. (7.1 mil)
8 Pt. Liner	White boardstock with printable backer. (8.0 mil)

^{*}Additional liners are available for custom orders. Please confect your DCM Sales Representative for details.



Statement of Practical Use: Per industry standards, all pressure sensitive and non-pressure sensitive materials should be thoroughly tested under actual end-use conditions to ensure that it meets the requirements of the specific application. DCM, Inc. will make no warranty, expressed or implied, pertaining to the functionality or performance of this construction without end user validation, whereby the standard period of warranty will take effect, being one year from purchase date.