



Product Specification Data

DCM ARTISAN CANVAS

REMOVABLE VINYL

Facestock: White, Flexible, Textured Vinyl

DCM's Artisan Canvas removable vinyl is thick, textured stock that mimics the look and feel of a painter's canvas. Artisan Canvas exhibits the same removability/repositionability of our classic Magik-Stik, but adds new layers of richness and complexity to your prints due to its textured feel.

Artisan Canvas is available in a 6.0 mil, white, textured facestock.

Adhesive: Proprietary Removable/Repositionable System

DCM's Artisan Canvas features our Magik-Stik adhesive system; a proprietary, water-based formulation that is perfect for applications that require both superior tack and clean removability. This adhesive works great on a variety of surfaces such as painted drywall, glass, metal, sanded wood (w/o lacquer), and most any non-textured or non-porous wall.

The minimum application temperature for DCM Artisan Canvas is 40°F, with a service temperature range of 40°F to 120°F.

Liner:

DCM Artisan Canvas is available on a 92# double-sided, poly-coated liner.

		Stocked Liners				
		50#	78#	83#	92#	8 Pt.
Facestock:	6.0 Textured White				X	

Item	Description
50# Liner	Semi-bleached, super-calendared, white kraft. (3.1 mil)
78# Liner	Clay-coated, super-calendared on one side, silicone-coated on the clay-coated side. (4.6 mil)
83# Liner	Silicone liner, clay-coated on both sides. (5.8 mil)
92# Liner	Heavyweight, bleached kraft, poly-coated on both sides. (7.1 mil)
8 Pt. Liner	White boardstock with printable backer. (8.0 mil)

*Additional liners are available for custom orders. Please contact your DCM Sales Representative for details.

Statement of Practical Use: Per industry standards, all pressure sensitive and non-pressure sensitive materials should be thoroughly tested under actual end-use conditions to ensure that it meets the requirements of the specific application. DCM, Inc. will make no warranty, expressed or implied, pertaining to the functionality or performance of this construction without end user validation, whereby the standard period of warranty will take effect, being one year from purchase date.

